



A Division of
South West Lubricants, Inc.

Material Safety Data Sheet
Maxima Suspension Clean

Last updated: June 2010

1. Product and Company Identification

Product Trade Name Maxima Suspension Clean
CAS Number Not applicable for mixtures
Synonyms None
Generic Chemical Name Emulsion (mixture)
Product Type Suspension Internal Cleaner
Transportation Emergency CHEMTREC 1-800-424-9300 (Outside USA 703-527-3887)
MSDS No. 71920

2. Composition/Information on Ingredients

Common Name	Chemical Name	CAS No.	Range (%)
N-Hexane		110-54-3	40-100
Carbon Dioxide		124-38-9	1-5

3. Hazards Identification

EMERGENCY OVERVIEW

Warning! Extremely Flammable. Contents under pressure. Container may burst if heated.

Do not place in hot water or near radiators, stoves or other sources of heat. Do not puncture or incinerate container or store at temperatures over 120°F. Do not use in presence of open flame, spark or other sources of ignition. KEEP OUT OF REACH OF CHILDREN. Avoid getting into eyes. Use only as directed.

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

IMMEDIATE HEALTH EFFECTS

Eye Vapors may irritate the eye and liquid may cause moderate irritation and slight corneal injury.
Skin Components are readily absorbed through the skin and repeated contact may result in drying of the skin which may result in skin irritation and dermatitis.
Ingestion Swallowing can cause irritation, nausea and vomiting. No harmful or chronic affects are expected to occur from a single accidental ingestion.
Inhalation High vapor concentrations are irritating to the nose, throat, mucous membrane and lungs. May cause headaches, dizziness, sleep and may have other central nervous system effects.

4. First Aid Measures

Eye If liquid gets into eyes, flush with clear water for 15 minutes or until irritation subsides. As a precaution, remove contact lenses, if worn. If irritation persists, call a physician.
Skin Remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.
Ingestion Do not induce vomiting. As a precaution, give the person a glass of water or milk to drink and get medical advice. Never give anything by mouth to an unconscious person.
Inhalation If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.



A Division of
South West Lubricants, Inc.

Material Safety Data Sheet
Maxima Suspension Clean

Last updated: June 2010

5. Fire Fighting Measures

FIRE CLASSIFICATION:

Aerosol – Consumer Commodity ORM-D. Extremely flammable! CFR 16, Ch. II, sub-chapter C, part 15.45.

Aerosol Level 3. Reference to NFPA 30B, section 1-7 of Aug.6, 1998. *Code for the Manufacture and Storage of Aerosol Products.*

NFPA RATINGS Health: 1 Flammability: 4 Reactivity: 0

FIRE and EXPLOSION HAZARDS Do not spray near open flame. Keep at room temperature as exposure to direct sunlight or other heat may cause bursting (aerosol.)

FLAMMABLE PROPERTIES:

Flash Point Propellant below 20°F (T.O.C.)
Autoignition ND
Flammability (Explosive) Limits (% by volume in air) Lower: NA Upper: NA

EXTINGUISHING MEDIA Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames. Use water to keep fire-exposed containers cool. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for persons attempting to stop a leak. Minimize breathing of gases, vapor, fumes or decomposition products.

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

6. Accidental Release Measures

Protective Measures Eliminate all sources of ignition in vicinity of spilled material.

Spill Management Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.

Reporting Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at (800) 424-8802 as appropriate or required.



A Division of
South West Lubricants, Inc.

Material Safety Data Sheet
Maxima Suspension Clean

Last updated: June 2010

7. Handling and Storage

- Handling** Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water. Wear recommended protective equipment. Practice good personal hygiene after handling.
- Storage** Store in closed containers of proper construction. Store away from sources of ignition and in areas of good ventilation. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Empty containers should be completely drained, properly closed, and promptly returned to a drum conditioner or disposed of properly.

8. Exposure Controls/Personal Protection

- Exposure Limits** ACGIH TLV (N-Hexane) TWA = 50 ppm; OSHA PEL (N-Hexane) TWA = 500 ppm
- Ventilation** Use in areas of adequate ventilation. Use mechanical exhaust to control vapors or mists.
- Gloves** Use nitrile or neoprene gloves.
- Eye Protection** Safety glasses, goggles or face shield are recommended.
- Respiratory** Use NIOSH/MSHA approved respirator with organic vapor cartridge and dust/mist cartridge is recommended if exposure limit is exceeded. Self-contained breathing apparatus is recommended for confined space entry.
- Clothing** Long sleeve shirt and apron when potential for skin contact. Wear neoprene or nitrile rubber boots when necessary to avoid contaminating shoes.

9. Physical and Chemical Properties

- | | |
|--------------------------------|---|
| Appearance and Odor | Clear liquid, solvent odor |
| pH | ND |
| Vapor Pressure | 100 - 120 psig @ 70°F. (Finished Product) |
| Vapor Density (Air = 1) | <1 |
| Boiling Point | <160°F (71°C) (Concentrate Only) |
| Solubility | Insoluble |
| Freezing Point | NA |
| Melting Point | NA |
| Specific Gravity | 0.675 @ 60°F (15.5°C) |
| Weight per Gallon | 5.62 #/gal |
| Viscosity | ND |

10. Stability and Reactivity Data

- Chemical Stability** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. Do not store above 120°F.



A Division of
South West Lubricants, Inc.

Material Safety Data Sheet
Maxima Suspension Clean

Last updated: June 2010

- Incompatibility With Other Materials** May react with strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
- Hazardous Decomposition Products** None known (None expected)
- Hazardous Polymerization** Hazardous polymerization will not occur.

11. Toxicological Information

- Toxicity** Mixture; Not determined
- Eye Irritation** May cause slight to moderate eye irritation
- Skin Irritation** Not expected to be a primary skin irritant. Prolonged or repetitive contact may cause irritation.
- Acute Oral Toxicity** Swallowing material may cause irritation of the gastrointestinal lining, nausea, vomiting, diarrhea and abdominal pain.
- Carcinogenic** This material has not been identified as a carcinogen by NTP, IARC or OSHA.
- Genetic Toxicity** Not determined.

ADDITIONAL TOXICOLOGY INFORMATION

This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking or severe hydrotreating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B).

12. Ecological Information

None found.

13. Disposal Considerations

- Disposal** Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Consult federal, state and local regulations regarding disposal methods. Do not contaminate oil with solvents or other chemicals.



A Division of
South West Lubricants, Inc.

Material Safety Data Sheet
Maxima Suspension Clean

Last updated: June 2010

14. Transport Information

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

Ground

DOT Shipping Name NOT REGULATED AS A HAZARDOUS MATERIAL FOR
TRANSPORTATION UNDER 49 CFR
DOT Hazard Class CONSUMER COMMODITY ORM-D
DOT Identification Number UN1950 (aerosol)
DOT Packing Group PG II

Overseas

IMDG Shipping Name AEROSOLS, LIMITED QUANTITY
IMDG Hazard Class 2
IMDG UN No. 1950

Air

IATA Shipping Name CONSUMER COMMODITY
IATA Class 9
IATA ID No. ID8000
IATA Label MISCELLANEOUS DANGEROUS GOODS CLASS 9
IATA Packing Instructions 910

15. Regulatory Information

TSCA Not listed

SARA 313 This product does not contain greater than 1.0% of any chemical substance on the SARA Extremely Hazardous Substances list.

CAL PROP 65 Not listed

16. Other Information

NFPA RATINGS Health: 1 Flammability: 4 Reactivity: 0
HMIS RATINGS Health: 1 Flammability: 4 Reactivity: 0

(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.